THIRD-ORDER LEVELING SEA LEVEL DATUM OF 1929 36-084-12 JELLICO QUADRANGLE 6 KY.-200 TENN. N3630-W8400/15 DIAGRAM NJ 16-12 CORBIN

FONDE

(5 KY.-199 TENN.)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY


Whitley County, Kentucky; Campbell, Claibourne, Counties, Tennessee

Final adjustment of 1951

Edition of 5/16/74

PR: WSM/sws

CORBIN (34)



STEARNS (7 KY.-201 TENN.)

LA FOLLETTE (167)

#### NGS (USC&GS) VERTICAL CONTROL DATA

A. Quadrangle 360841

6 KY.-200 TENN.
JELLICO QUADRANGLE

36-084-12 N3630-W8400/15

#### INDEX OF PERMANENT MARKS

MARKS (USGS)	PAGE NO.	MARKS (USGS)	PAGE NO.
к 6	3	K 7 1924	3
K 4 1924	3	K 5 1925	. 3

	-
ISOLATED BENCH MARKS (By H. R. Kilmer, 1924; Book B1950)	Feet
La Follette, 12.6 mi N. of; 5 ft E. of rd.; in flat boulder at Lowels Creek; standard tablet stamped "K 4 1924"	1241.211
La Follete, 16.3 mi N. of; top of Pine Mountain; 20 ft S. of rd.; in rock ledge; standard tablet stamped "K 5 1925"	1838.699
Jellico; at main entrance to post office; in top of NW. corner of stone post on N. side of entrance steps $2\frac{1}{2}$ ft higher than ground; standard tablet stamped "K 6" (Tied by NGS)	981.947
<pre>Jellico, 11.7 mi S. of; on Hickory Creek; 20 ft N. of rd.; in boulder 3 ft higher than ground; standard tablet stamped "K 7 1924" (Reported destroyed, 1953)</pre>	1117.532

# UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

36-084-12
JELLICO QUADRANGLE
6 KY.-200 TENN.
N3630-W8400/15
DIAGRAM NJ 16-12
CORBIN

McCreary and Whitley Counties, Ky.; Campbell, Claiborne, and Scott Counties, Tenn.

Edition of 6/21/76

PR: CRY/rmm

Plane coordinates are based on Lambert projection, Kentucky, South Zone and Tennessee Zone Only the permanent marks are listed for control classified obsolete and are not shown on sketch

	CORBIN (34)			
			2	
			~	
				FONDE (5 KY199 TEN
KENTUCKY	* .: .			
TENNESSEE	⊞ Jellico			
			84°00'	
	LA FOLLETTE	36°30'		

(167)

STEARNS (7 KY.-201 TENN.)

#### DISCLAIMER

We no longer attest to the validity of the positions listed for horizontal control established by transit traverse procedures. This control is now considered OBSOLETE and is included in this list for the purpose of identification only.

#### INDEX OF PERMANENT MARKS

MARK (USGS)	PAGE NO.
IT 129 E 1930 IT 130 E 1930 IT 131 E 1930 IT 132 E 1930 IT 19 BT 1951 IT 20 BT 1951 IT 21 BT 1951 IT 35 BT 1951 IT 36 BT 1951 IT 40 DWP 1951 IT 41 DWP 1951	3 3 3 6 6 6 5 5 4 4
TT 42 DWP 1951	4
TENNESSEE DIVISION OF GEOLOGY	
LHT 1755 1941	4
NGS	
G 51 1934 H 51 1934 J 51 1934 K 51 1934 M 49 1935 970.713 P 49 1935 977.469 Q 49 1935 R 49 1935 S 49 1935 963.404 T 49 1935 971.606 U 49 1935 977.009 V 49 1935 966.694 X 49 1935 967.465 V 192 1950 937.820	4 4 5 5 6 3 5 3 6 5

STATION DESCRIPTION PLANE COORDINATES. FEET

LATITUDE 0 1 11 LONGITUDE 0 1 #

The following positions are considered OBSOLETE. To be used only to locate permanent marks in the field.

By J. R. Ellis, 1930; Book C9693

Newcomb, 3.1 mi SW. of, along Southern Railway; 25 ft W. of centerline of track; in sandstone outcrop; standard tablet stamped "TT 129 E 1930"

Ky. S.) X = 2.455.051

Y = 71.195

36 31 07.10

84 12 05.49

Newcomb; at public school; in lower front concrete step at entrance; standard tablet stamped "TT 130 E 1930" (Reported destroyed, 1977)

X = 2.464.393

Y = 84.276

36 33 14.90

84 10 08.63

Newcomb, about 2.8 mi NW. of; 1.5 mi up Trammel Branch from junction of Newcomb—Capuchin Road with Capuchin Creek; on S. side of rd.; in large sandstone outcrop (trail leaves rd. at this point); standard tablet stamped MIT 131 E 1930"

X = 2.452.034

Y = 87.213

36 33 45.95

84 12 39.24

Zion Hill; at church and schoolhouse; 0.3 mi below mouth of Capuchin Creek; 70 ft E. of centerline of rd. at iunction of I-rd. W.: in sandstone outcrop; standard tablet stamped "TT 132 E 1930"

X = 2.444.138

Y = 103.981

36 36 32.99

84 14 12.72

By D. W. Pinkston, 1951; Book AH 244

Lot, 52 ft SW. of, and across SW. track from W. corner of Louisville and Nashville Railroad flag station: 30 ft SW. of and 3 ft lower than SW. rail of SW. one of two tracks; 87 ft W. of, and across track from W. corner of small telephone booth; in rock outcrop; NGS standard disk stamped "V 49 1935 966.694"

X = 2.485.446 Y = 101.373

36 36 00.36

84 05 46-74

Lot. about 0.2 mi N. of station, along L. & N. RR.; at RR. bridge No. 58 over State Highway 471; 6 ft E. of, and 2 ft lower than E. rail of track; in E. end of S. abutment of overpass; NGS standard disk stamped "U 49 1935 977.009"

X = 2.485.514 Y = 102.543

36 36 11.92

84 05 45.66

Saxton, 1.7 mi S. of station, along L. & N. RR.; 1.2 mi N. of Lot; 7 ft E. of, and 2 ft lower than E. rail of track; at RR. bridge No. 57 over creek; in E. end of S. concrete abutment; NGS standard disk stamped "T 49 1935 971.606"

X = 2.486.474 Y = 106.756

36 36 53.40

84 05 32.99

Saxton, 41 ft SE. of SE. corner of L. & M. RR. station; 17 ft W. of, and 1 ft lower than W. rail of track; 4 ft N. of telephone pole; in concrete post; NGS standard disk stamped "R 49 1935"

X = 2.480.821

Y = 112,975

36 37 55.86

84 06 40.99

STATION DESCRIPTION PLANE COORDINATES, FEET

LAT ITUDE 0 9 11

LONGITUDE

## OBSOLETE MARKS (Cont'd.)

Jellico, 3.9 mi SE. of, along U. S. Highway 25 W.; 22 ft S. of centerline of hwy.; 260 ft N. of NE. corner of Sandy Beach Cafe; 4 ft SE. of telephone pole; in concrete post; standard tablet stamped "TT 40 DWP 1951"

Ky. S.) X = 2.493.267

Y = 92,683

36 34 33.09

84 04 12.75

Holton, 7 rails W. of L. & N. RR. station; 5 ft S. of S. rail of track; 4 rails E. of portal of tunnel on wye; 2.5 rails W. of milepost L-206; in concrete post; NGS standard disk stamped "K 51 1934"

X = 2,503,374 Y = 88,644

36 33 51.35

84 02 09.76

Morley, 84 ft SW. of L. & N. RR. station; 52 ft NW. of main track; 1 ft E. of fence; in concrete post; NGS standard

X = 2,499,846 Y = 83,805

36 33 04.15

84 02 54-08

Chaska, 1.6 mi NE. of, along L. & N. RR.; at bridge No. 69; in N. end of backwall of E. abutment; NGS standard

X = 2.492.395 Y = 80.576

36 32 33.54

84 04 26.07

Chaska, at water tank; in NE. one of two E. concrete pedestal stones, midway between N. and S. edges; NGS standard

X = 2.491.539 Y = 75.589

36 31 44.39

84 04 37.64

Chaska, 1.1 mi S. of, along U. S. Highway 25 W.; 0.6 mi N. of large concrete bridge over Hickory Creek; 98 ft NW. of junction of I-rd. W.; 27 ft E. of centerline of hwy.; 23 ft S. of telephone pele; 3 ft N. and 1 ft W. of fence corner; in concrete post; standard tablet stamped "TT 41 DWP 1951"

X = 2.489.478 Y = 70.250

36 30 51.96

84 05 04.04

Chaska, 1.6 mi S. of, along U. S. Highway 25 W., thence 1.0 mi W. along county rd.; 0.4 mi E. of Watsons Store; 50 ft N. of centerline of rd.; in concrete post; Tennessee Division of Geology standard disk stamped

X = 2,485,815 Y = 66,860

36 30 19.08

84 05 49.63

Chaska, 1.6 mi S. of, along U. S. Highway 25 W., thence 1.4 mi W. along county rd.; 18 ft S. and 32 ft E. of centerline of rd. at junction of I-rd. N.; 1 ft S. and 2 ft E. of NE. corner of Watsons Store; in concrete post; standard tablet stamped "TT 42 DWP 1951"

X = 2,484,254 Y = 66,366

36 30 14.47

84 06 08.85

STATION DESCRIPTION PLANE COORDINATES, FEET

LATITUDE 0 1 11 LONGITUDE 0 1 . 11

#### OBSOLETE MARKS (Cont'd.)

By M. L. Bennett, 1951; Books MS 30344, 30347, 30348 (TVA)

Williamsburg, 1.0 mi SE. of, along U. S. Highway 25 W.; 108 ft NW. of junction of State Highway 92 E.; 47 ft W. of, and 3 ft higher than centerline of Highway 25 W.; 13 ft E. of centerline of graveled drive paralleling hwy.; 131 ft N. of NE. corner of concrete block building; 2 ft E. of white wooden witness post; NGS standard disk stamped "V 192 1950 937.820"

Ky. S.) X = 2.467.459

Y = 149.567

36 43 59.90

84 09 17.31

Williamsburg, 2.2 mi SE. of, along U. S. Highway 25 W.; 0.3 mi NW. of Emlyn; 70 ft N. and 25 ft W. of centerline of hwy. at junction of Y-rd. NW.; 75 ft S. of L. & N. RR. milepost No. L-192; 58 ft NW. of telephone pole; in concrete post; standard tablet stamped "TI 35 BT 1951"

X = 2,468,739 Y = 140,984

36 42 34-82

84 09 03.37

Savoy, 1.4 mi S. of station, along L. & M. RR.; at macadam rd. crossing and post office at Emlyn; SSE. of, and across rd. from post office; 46 ft E. of, and 1 ft lower than E. rail of track; 20 ft S. of centerline of macadam rd.; 11 ft S. of power pole and fence corner; 1 ft W. of fenceline; in concrete post; NGS standard disk stamped "M 49 1935 970.713"

X = 2.471.012 Y = 138.975

36 42 14.58

84 08 35.89

Emlyn, 2.3 mi SE. of, along U. S. Highway 25 W.; at Pleasant View; 38 ft N. and 36 ft E. of centerline of hwy. at junction of drive E.; 50 ft NW. of corner of white house; 7 ft NW. of white cross on telephone pole; in concrete post; standard tablet stamped "IT 36 BT 1951"

X = 2,475,286

Y = 129,798

36 40 43.13

84 07 45 34

Mountain Ash, 0.2 mi S. of station, along L. & N. RR.; at RR. bridge over Clear Fork River; 8 ft W. of, and 3 ft lower than W. rail of track; 1 ft S. of M. end of abutment; in NW. end of SW. abutment; NGS standard disk stamped "P 49 1935 977.469"

X = 2.475.064 Y = 120.585

36 39 12.08

84 07 50.00

Saxton, O.1 mi SW. of L. & M. RR. station; at point where RR. has been abandoned and is now graveled rd.; at bridge No. 54 over creek; 4 ft W. of old roadbed; in W. end of N. abutment; NGS standard disk stamped "S 49 1935 963.404" (Bridge reported destroyed but abutment remains)

X = 2.480.913

Y = 112,274

36 37 48.92

84 06 40.01

STATION DESCRIPTION PLANE COORDINATES, FEET

LATITUDE 0 1 11

LONGITUDE

## OBSOLETE MARKS (Cont'd.)

Saxtom, O.l mi N. of station, along L. & N. RR.; at bridge over U. S. Highway 25 W.; 7 ft E. of, and 2 ft lower than E. rail of track; in E. end of S. abutment; NGS standard disk stamped "Q 49 1935"

Ky. S.) X = 2,480,511

Y = 113,320

36 37 59.32

84 06 44.71

Lot, 0.8 mi SE. of station, along L. & M. RR.; 7 rails N. of Kentucky-Tennessee State line marker; 7 ft E. of, and 2 ft lower than E. rail of track; in concrete signal base; NGS standard disk stamped "X 49 1935 967.465"

X = 2,488,430 Y = 98,243

36 35 28.90

84 05 10.83

Siler, 0.6 mi S. of post office, along State Highway 92, thence 5.8 mi SW. along Mud Creek Road; 17 ft SE. of centerline of rd.; 56 ft ME. of apple tree; 9 ft SW. of persimmon tree; 2 ft NW. of fenceline; in concrete post; standard tablet stamped "TI 19 BI 1951"

X = 2.512.059

Y = 110,899

36 37 29.81

84 00 18.29

Siler, 0.6 mi S. of post office, along State Highway 92, thence 7.7 mi SW. along Mud Creek Road; at Sulphur Spring Baptist Church; 68 ft SW. of centerline of rd. at junction of rd. SW.; 60 ft NE. of SE. corner of church; 15 ft SE. of 15-in. sycamore tree; in concrete post; standard tablet stamped "TT 20 BT 1951"

X = 2,504,150

Y = 105,106

36 36 33,97

84 01 56.58

Jellico, 2.4 mi E. of, along U. S. Highway 25 W., thence 1.9 mi NE. along Cumberland Valley Road; 12 ft N. of centerline of rd.; 42 ft NE. of nail and washer in 8-in. pine tree in fenceline; 33 ft NW. of nail and washer in 4-in. pine tree on top of bank; 3 ft S. of fenceline; in concrete post; standard tablet stamped "TT 21 BT 1951"

X = 2.495.128

Y = 99,687

36 35 42,00

84 03 48,40